



Capacity (kg)	Increment (kg)
500	0,1
2000	0,5
3200	0,5
6300	1
8000	2
10000	2



TECHNICAL DATA DR10

- For scale operation, data transfer and weighing result viewing through radio
- Menu based interface
- Easy-to-use keyboard
- Summing function
- Nonvolatile memory for 1000 weighing results with time and date
- Charge level display for scale and DR10
- Operation temperature: -10°C...+55°C
- Graphic LCD display (64x128 mm) with white LED backlight
- Operation range: 200 m on line of sight
- Radio frequency: 433.23 Hhz-434.35 Mhz
- 10 user selectable radio channels
- Radio RF power: 1-10 mW
- Operation time: - with backlight: 34 h
- without backlight 65 hours
- Battery type: 2 x NiMh AA, 2100 mAh
- USB port for charging and data upload to PC
- Charging time: 5 hours
- Delivery includes USB cable
- Weight: 200 g

Options for PCS scale

- DR10 radio remote control unit
- Infra red remote control
- Radio transmission to PC
- Approved model for commercial weighing
- Summing function
- Log memory for data saving
- LED display

Delivery includes

- Battery
- Charger
- Lifting ring
- Safety hook
- Test certificate

Capacity (kg)	Dimensions (mm)								
	A	B	C	D	E	F	G	H	I
500	200	181	110	427	28	60	16	110	170
2000	200	181	110	427	28	60	16	110	170
3200	200	181	110	477,5	33	75	18	135	170
6300	200	181	110	545	40	90	23	160	170
8000	200	181	110	599	49	100	27	180	170
10000	200	181	110	599	49	100	27	180	170

TECHNICAL DATA PCS SCALE

- Accuracy: $\pm 0.05\%$ of capacity
- Load cell breaking strength: 500 % of capacity
- Allowed peak load: 200 % of capacity
- Taring range: 100 % of capacity
- Working temperature: -20°C...+50°C
- Display: 4 digit, 25 mm high LCD with backlight
- Push buttons: On/Off, Tare, G/N, Light, Zero
- Battery operated maintenance free
- Operation time: 200 h per full charge
- Battery type: 6V/3Ah, rechargeable
- External charger: 230V-50Hz, charging time 8h
- Internal protection against overcharging
- Battery voltage indication in ten steps when starting scale
- Low battery voltage warning during operation
- Automatic zeroing and check-up when starting scale
- Overload indication if load exceeds capacity by 9 increments
- Automatic power off if not used for 10 minutes
- Real time clock, date and time
- Cast aluminum case IP 65 tested for out-door use